



IDC-6060DHA-02 & IDC-6060DHA-TH

5X5 DISPLAY HEAD ASSEMBLY FOR AIRBORNE APPLICATIONS



The Display Head Assembly (DHA) contains:

- 5.0 x 5.0 inch LCD
- AR Protective Glass
- Direct & Edge LED Backlight Versions
- Backlight Controller Board
- LCD Heater (Optional)
- Frame Designed for Harsh Environments
- Extended Temperature Range
- Full Sunlight Readability
- High Luminance
- Wide Viewing Angle
- High Contrast
- 8-bit Digital RGB Signals
- Standard 47mm (-02 version) and Thin 15.6mm (-TH version) Housing Design
- Wide Dimming Range
- Night Vision Filter (Optional)

General Characteristics	
Display Area	126.9 mm (w) x 126.9 mm (h) [5.0 in (w) x 5.0 in (h)]
Diagonal Size of Display	179.5 mm [7.1 in]
Drive System	a-Si TFT Active Matrix
Display Color	16,777,216 colors (8 bits)
Pixel Resolution	600 (H) x 600 (V)
Sub-Pixel Resolution	1,800 (H) x 600 (V)
Pixel Configuration	R G B Stripe (Red, Green, Blue stripe)

www.idclcd.com (770) 886-3960

1115 Alpha Drive, Alpharetta, GA 30004

www.idclcd.com (770) 886-3960

1115 Alpha Drive, Alpharetta, GA 30004